

SOYBEAN OIL EXPORT STANDARD

NCM: 15.07.1000



ABOUT THE PRODUCT

Soybean (Glycine max.) oil, export standard.

PURPOSES OF USE

Soybean oil is a result of soybean processing. The product is obtained from the processes of preparation and extraction. It is commonly used in animal nutrition, refining, fuel, among others.

PROCESSING

- a) Pre-cleaning;
- b) Post-cleaning;
- c) Drying (when necessary);
- d) Grinding;
- e) Cooking
- f) Rolling
- g) Expansion;
- h) Hexane oil extraction;
- i) Filtering
- j) Degumming.

TRADE NAMES

- ▶ Soybean oil;
- ▶ Soybean degummed oil;
- ▶ Soybean oil for refining;
- ▶ Soybean filtered oil;
- ▶ Glycine max. oil.

CHARACTERISTICS

Description	Ref. Value	Analysis Method
Ethereal extract	Min. 960 g/kg	According to IN 49/2006
Acidity (oleic, molecular weight 282)	Max. 1% g/kg	AOCS Ca 5a-40
Moisture and volatile matter	Max. 0.2% g/kg	AOCS Ca 2c-25
Impurities and foreign matter	Max. 0.1% mg/kg	AOCS Ca 3a-46
Lectin (exposed as phosphorus)	Max. 0.2%	AOCS Ca 12-55
Unsaponifiable matter (N.S.P.A. test)	Max. 1.5%	AOCS Ca 6a-40
Staining (1st Lovibond cell)	No darker than 50 and 5 red	AOCS Cc 13b-45
Peroxide value	Max. 15.0 meg/1000g	According to IN 49/2006

STORAGE

In steel tanks, out of the reach of light (preferably at or below 25°C).

SUPPLY

Bulk in isotanks; and soft plastic flexitanks.

TRANSPORTATION

In bulk or according to packaging specifications.



SUBMIT A BUDGET REQUEST

- ✉ contato@bomm.com.br
- 🌐 www.bomm.com.br
- ☎ (44) 3649 1240
- 📍 Rua Dom Pedro I, n. 1190, Escritório, Centro
CEP 85950-000, Palotina, Paraná